2-Propanol CMOS

(iso-propyl alcohol)





Material No.: 9079-05 Batch No.: 0000102906 Manufactured Date: 2014/09/26 Retest Date: 2019/09/25

Certificate of Analysis

Test	Specification	Result
ssay (CH3CHOHCH3)	>= 99.5 %	100.0
Color (APHA)	<= 10	5
esidue after Evaporation	<= 4 ppm	< 1
olubility in H2O	Passes Test	PT
/ater (H2O)(by Karl Fischer titrn)	<= 0.05 %	0.02
cidity (µeq/g)	<= 0.2	0.1
lkalinity (µeq/g)	<= 0.1	< 0.1
hloride (Cl)	<= 0.1 ppm	< 0.1
hosphate (PO4)	<= 0.3 ppm	< 0.3
race Impurities – Aluminum (Al)	<= 50.0 ppb	< 5.0
rsenic and Antimony (as As)	<= 10 ppb	< 10
race Impurities – Barium (Ba)	<= 20.0 ppb	< 1.0
race Impurities – Beryllium (Be)	<= 100.0 ppb	< 1.0
race Impurities – Bismuth (Bi)	<= 100.0 ppb	< 10.0
race Impurities – Boron (B)	<= 10.0 ppb	< 5.0
race Impurities – Cadmium (Cd)	<= 20.0 ppb	< 1.0
race Impurities – Calcium (Ca)	<= 50.0 ppb	1.3
race Impurities – Chromium (Cr)	<= 20.0 ppb	< 1.0
race Impurities - Cobalt (Co)	<= 20.0 ppb	< 1.0
race Impurities – Copper (Cu)	<= 10.0 ppb	< 1.0
race Impurities – Gallium (Ga)	<= 50.0 ppb	< 1.0
race Impurities – Germanium (Ge)	<= 50.0 ppb	< 10.0
race Impurities – Gold (Au)	<= 20.0 ppb	< 5.0
leavy Metals (as Pb)	<= 200 ppb	< 200

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610

Test	Specification	Result
Frace Impurities – Iron (Fe)	<= 50.0 ppb	< 1.0
Frace Impurities – Lead (Pb)	<= 20.0 ppb	< 10.0
Frace Impurities – Lithium (Li)	<= 50.0 ppb	< 1.0
Frace Impurities – Magnesium (Mg)	<= 20.0 ppb	< 1.0
Frace Impurities – Manganese (Mn)	<= 15.0 ppb	< 1.0
Frace Impurities – Molybdenum (Mo)	<= 100.0 ppb	< 5.0
Frace Impurities – Nickel (Ni)	<= 10.0 ppb	< 5.0
Frace Impurities – Niobium (Nb)	<= 100.0 ppb	< 1.0
Frace Impurities – Potassium (K)	<= 100.0 ppb	< 10.0
Frace Impurities – Silicon (Si)	<= 50.0 ppb	< 10.0
Frace Impurities – Silver (Ag)	<= 20.0 ppb	< 1.0
Frace Impurities – Sodium (Na)	<= 100.0 ppb	< 5.0
Frace Impurities – Strontium (Sr)	<= 20.0 ppb	< 1.0
Frace Impurities – Tantalum (Ta)	<= 100.0 ppb	< 5.0
Frace Impurities – Thallium (Tl)	<= 10.0 ppb	< 5.0
Frace Impurities – Tin (Sn)	<= 100.0 ppb	< 10.0
Frace Impurities – Titanium (Ti)	<= 20.0 ppb	< 1.0
Frace Impurities – Vanadium (V)	<= 100.0 ppb	< 1.0
Frace Impurities – Zinc (Zn)	<= 50.0 ppb	< 1.0
Frace Impurities – Zirconium (Zr)	<= 100.0 ppb	< 1.0
Particle Count – 0.2 µm and greater	<= 5000 par/ml	1348
Particle Count – 0.3 µm and greater	<= 5000 par/ml	208
Particle Count – 0.5 µm and greater	<= 50 par/ml	23
Particle Count - 1.0 µm and greater	<= 8 par/ml	5

For Microelectronic Use

Country of Origin:USPackaging Site:Paris Mfg Ctr & DC



Phillipsburg, NJ 9001:2008, 14001:2004, FSSC 22000 Paris, KY 9001:2008 Mexico City, Mexico 9001:2008 Deventer, The Netherlands 9001:2008, 14001:2004, 13485:2003 Gliwice, Poland 9001:2008, 17025:2005 Selangor, Malaysia 9001:2008 Dehradun, India, 9001:2008, 14001:2004, 13485:2003 Mumbai, India, 9001:2008, 17025:2005 Panoli, India 9001:2008

Nel M Sac

Richard M Siberski Vice President Global Quality

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610