

Acetic Acid, Glacial
CMOS



Material No.: 9503-03
Batch No.: 0000122541
Manufactured Date: 2015/09/01
Retest Date: 2020/08/30

Certificate of Analysis

Test	Specification	Result
Assay (CH ₃ COOH) (by freezing point)	>= 99.7 %	100.0
Color (APHA)	<= 10	5
Acetic Anhydride ((CH ₃ CO) ₂ O)	<= 0.01 %	< 0.01
Acetaldehyde	<= 0.05 %	< 0.05
Residue after Evaporation	<= 4 ppm	< 1
Solubility in H ₂ O	Passes Test	PT
Specific Gravity at 20°/20°C	>= 1.048	1.051
Substances Reducing Dichromate	Passes Test	PT
Substances Reducing Permanganate	Passes Test	PT
Chloride (Cl)	<= 0.5 ppm	< 0.5
Phosphate (PO ₄)	<= 0.5 ppm	< 0.3
Sulfate (SO ₄)	<= 0.5 ppm	< 0.3
Trace Impurities – Aluminum (Al)	<= 50.0 ppb	3.0
Arsenic and Antimony (as As)	<= 5 ppb	< 5
Trace Impurities – Barium (Ba)	<= 10.0 ppb	< 1.0
Trace Impurities – Beryllium (Be)	<= 10.0 ppb	< 0.2
Trace Impurities – Bismuth (Bi)	<= 50.0 ppb	< 1.0
Trace Impurities – Boron (B)	<= 10.0 ppb	< 0.7
Trace Impurities – Cadmium (Cd)	<= 10.0 ppb	< 1.0
Trace Impurities – Calcium (Ca)	<= 200.0 ppb	8.0
Trace Impurities – Chromium (Cr)	<= 30.0 ppb	4.0
Trace Impurities – Cobalt (Co)	<= 10.0 ppb	< 0.3
Trace Impurities – Copper (Cu)	<= 20.0 ppb	< 1.0
Trace Impurities – Gallium (Ga)	<= 10.0 ppb	< 1.0

Test	Specification	Result
Trace Impurities – Germanium (Ge)	<= 10.0 ppb	< 10.0
Trace Impurities – Gold (Au)	<= 10.0 ppb	< 5.0
Heavy Metals (as Pb)	<= 300 ppb	< 300
Trace Impurities – Iron (Fe)	<= 100.0 ppb	14.0
Trace Impurities – Lead (Pb)	<= 100.0 ppb	< 10.0
Trace Impurities – Lithium (Li)	<= 10.0 ppb	< 1.0
Trace Impurities – Magnesium (Mg)	<= 50.0 ppb	< 2.0
Trace Impurities – Manganese (Mn)	<= 10.0 ppb	< 1.0
Trace Impurities – Molybdenum (Mo)	<= 10.0 ppb	< 5.0
Trace Impurities – Nickel (Ni)	<= 25.0 ppb	< 5.0
Trace Impurities – Niobium (Nb)	<= 10.0 ppb	1.0
Trace Impurities – Potassium (K)	<= 100.0 ppb	< 10.0
Trace Impurities – Silicon (Si)	<= 50.0 ppb	12.0
Trace Impurities – Silver (Ag)	<= 10.0 ppb	< 1.0
Trace Impurities – Sodium (Na)	<= 100.0 ppb	7.0
Trace Impurities – Strontium (Sr)	<= 10.0 ppb	< 1.0
Trace Impurities – Tantalum (Ta)	<= 10.0 ppb	< 5.0
Trace Impurities – Thallium (Tl)	<= 50.0 ppb	< 5.0
Trace Impurities – Tin (Sn)	<= 50.0 ppb	< 10.0
Trace Impurities – Titanium (Ti)	<= 100.0 ppb	< 1.0
Trace Impurities – Vanadium (V)	<= 10.0 ppb	< 1.0
Trace Impurities – Zinc (Zn)	<= 50.0 ppb	9.0
Trace Impurities – Zirconium (Zr)	<= 10.0 ppb	< 1.0
Particle Count – 1.0 µm and greater	<= 10 par/ml	5

For Microelectronic Use

For additional information, go to www.askavantor.com. Search keywords "freezing" and product name.

Storage Conditions: IMPORTANT: Material will freeze if stored below 17 °C (63°F).

Country of Origin: US

Packaging Site: Phillipsburg Mfg Ctr & DC

Phillipsburg, NJ 9001:2008, 14001:2004, FSSC 22000
 Paris, KY 9001:2008
 Mexico City, Mexico 9001:2008
 Deventer, The Netherlands 9001:2008, 14001:2004, 13485:2003
 Gliwice, Poland 9001:2008
 Selangor, Malaysia 9001:2008
 Dehradun, India, 9001:2008, 14001:2004, 13485:2003
 Mumbai, India, 9001:2008, 17025:2005
 Panoli, India 9001:2008

Jamie Ethier
 Vice President Global Quality

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600
 Avantor™ Performance Materials Inc.

3477 Corporate Parkway, Suite #200, Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610