Hydrochloric Acid VLSI





Material No.: 5367-03 Batch No.: 0000096708 Manufactured Date: 2014/10/30 Retest Date: 2019/10/29

Certificate of Analysis

Test	Specification	Result
Assay (as HCl) (by acid-base titrn)	37.0 - 38.0 %	37.6
Color (APHA)	<= 10	6
Residue after Ignition	<= 3 ppm	1
Extractable Organic Substances	<= 3 ppm	< 1
Bromide (Br)	<= 0.005 %	< 0.005
Free Halogen (as Cl2)	Passes Test	PT
Ammonium (NH₄)	<= 1 ppm	< 1
Phosphate (PO4)	<= 0.05 ppm	< 0.03
Sulfate (SO4)	<= 0.3 ppm	0.3
Sulfite (SO₃)	<= 0.8 ppm	0.2
Frace Impurities – Aluminum (Al)	<= 100.0 ppb	< 5.0
Arsenic and Antimony (as As)	<= 5 ppb	< 3
Frace Impurities – Barium (Ba)	<= 20.0 ppb	< 1.0
Frace Impurities – Beryllium (Be)	<= 10.0 ppb	< 1.0
Frace Impurities – Bismuth (Bi)	<= 20.0 ppb	< 10.0
Frace Impurities – Boron (B)	<= 20.0 ppb	< 5.0
Frace Impurities – Cadmium (Cd)	<= 5.0 ppb	< 1.0
Frace Impurities – Calcium (Ca)	<= 100.0 ppb	44.8
Frace Impurities – Chromium (Cr)	<= 50.0 ppb	< 1.0
Frace Impurities – Cobalt (Co)	<= 5.0 ppb	< 1.0
Frace Impurities – Copper (Cu)	<= 5.0 ppb	< 1.0
Frace Impurities – Gallium (Ga)	<= 20.0 ppb	< 1.0
Frace Impurities – Germanium (Ge)	<= 20.0 ppb	< 10.0
Frace Impurities – Gold (Au)	<= 20.0 ppb	< 5.0

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610

Test	Specification	Result
leavy Metals (as Pb)	<= 100 ppb	<5
race Impurities – Iron (Fe)	<= 50.0 ppb	24.1
race Impurities – Lead (Pb)	<= 25.0 ppb	< 10.0
race Impurities – Lithium (Li)	<= 50.0 ppb	< 1.0
race Impurities – Magnesium (Mg)	<= 50.0 ppb	< 1.0
race Impurities – Manganese (Mn)	<= 5.0 ppb	< 1.0
race Impurities – Molybdenum (Mo)	<= 10.0 ppb	< 5.0
race Impurities – Nickel (Ni)	<= 10.0 ppb	< 5.0
race Impurities – Niobium (Nb)	<= 10.0 ppb	< 1.0
race Impurities – Potassium (K)	<= 100.0 ppb	< 10.0
race Impurities – Silicon (Si)	<= 100.0 ppb	< 10.0
race Impurities – Silver (Ag)	<= 20.0 ppb	< 1.0
race Impurities – Sodium (Na)	<= 100.0 ppb	9.2
race Impurities – Strontium (Sr)	<= 20.0 ppb	< 1.0
race Impurities – Tantalum (Ta)	<= 10.0 ppb	< 5.0
race Impurities – Thallium (TI)	<= 20.0 ppb	< 5.0
race Impurities – Tin (Sn)	<= 50.0 ppb	< 10.0
race Impurities – Titanium (Ti)	<= 10.0 ppb	< 1.0
race Impurities – Vanadium (V)	<= 10.0 ppb	< 1.0
race Impurities – Zinc (Zn)	<= 50.0 ppb	< 1.0
race Impurities – Zirconium (Zr)	<= 10.0 ppb	< 1.0
article Count – 0.5 µm and greater	<= 50 par/ml	2
article Count - 1.0 µm and greater	<= 10 par/ml	1

For Microelectronic Use

Reported value is the average of all samples counted for this lot number, with no individual sample value exceeding the specification.

Country of Origin: US Packaging Site: Paris Mfg Ctr & DC



Phillipsburg, NJ 9001:2008, 14001:2004 Paris, KY 9001:2008 Mexico City, Mexico 9001:2008 Deventer, The Netherlands 9001:2008, 14001:2004, 13485:2003 Gliwice, Poland 9001:2008, 17025:2005 Selangor, Malaysia 9001:2008 Dehradun, India, 9001:2008, 14001:2004, 13485:2003 Mumbai, India, 9001:2008, 17025:2005 Panoli, India 9001:2008

Nej M Sal

Richard M Siberski Vice President Global Quality

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610