

Sulfuric Acid 96%
VLSI



Material No.: 5374-03
Batch No.: 0000078141
Manufactured Date: 2014/03/17
Retest Date: 2019/03/16

Certificate of Analysis

Test	Specification	Result
Assay (H ₂ SO ₄)	95.0 - 97.0 %	96.2
Color (APHA)	<= 10	5
Chloride (Cl)	<= 0.1 ppm	0.1
Nitrate (NO ₃)	<= 0.2 ppm	0.1
Phosphate (PO ₄)	<= 0.3 ppm	< 0.1
Trace Impurities - Aluminum (Al)	<= 50.0 ppb	< 5.0
Arsenic and Antimony (as As)	<= 5 ppb	< 2
Trace Impurities - Barium (Ba)	<= 50.0 ppb	< 1.0
Trace Impurities - Beryllium (Be)	<= 10.0 ppb	< 1.0
Trace Impurities - Bismuth (Bi)	<= 20.0 ppb	< 10.0
Trace Impurities - Boron (B)	<= 10.0 ppb	< 5.0
Trace Impurities - Cadmium (Cd)	<= 50.0 ppb	< 1.0
Trace Impurities - Calcium (Ca)	<= 100.0 ppb	16.1
Trace Impurities - Chromium (Cr)	<= 50.0 ppb	3.2
Trace Impurities - Cobalt (Co)	<= 50.0 ppb	< 1.0
Trace Impurities - Copper (Cu)	<= 10.0 ppb	< 1.0
Trace Impurities - Gallium (Ga)	<= 20.0 ppb	< 1.0
Trace Impurities - Germanium (Ge)	<= 100.0 ppb	< 10.0
Trace Impurities - Gold (Au)	<= 40.0 ppb	< 5.0
Trace Impurities - Iron (Fe)	<= 200.0 ppb	5.1
Trace Impurities - Lead (Pb)	<= 20.0 ppb	< 10.0
Trace Impurities - Lithium (Li)	<= 50.0 ppb	< 1.0
Trace Impurities - Magnesium (Mg)	<= 50.0 ppb	< 1.0
Trace Impurities - Manganese (Mn)	<= 10.0 ppb	< 1.0

Test	Specification	Result
Trace Impurities – Molybdenum (Mo)	<= 10.0 ppb	< 5.0
Trace Impurities – Nickel (Ni)	<= 50.0 ppb	< 5.0
Trace Impurities – Niobium (Nb)	<= 10.0 ppb	< 1.0
Trace Impurities – Potassium (K)	<= 100.0 ppb	< 10.0
Trace Impurities – Silicon (Si)	<= 100.0 ppb	< 10.0
Trace Impurities – Silver (Ag)	<= 50.0 ppb	< 1.0
Trace Impurities – Sodium (Na)	<= 100.0 ppb	37.5
Trace Impurities – Strontium (Sr)	<= 10.0 ppb	< 1.0
Trace Impurities – Tantalum (Ta)	<= 10.0 ppb	< 5.0
Trace Impurities – Thallium (Tl)	<= 20.0 ppb	< 5.0
Trace Impurities – Tin (Sn)	<= 50.0 ppb	< 10.0
Trace Impurities – Titanium (Ti)	<= 10.0 ppb	2.0
Trace Impurities – Vanadium (V)	<= 10.0 ppb	< 1.0
Trace Impurities – Zinc (Zn)	<= 50.0 ppb	< 1.0
Trace Impurities – Zirconium (Zr)	<= 10.0 ppb	< 1.0
Particle Count – 0.5 µm and greater	<= 80 par/ml	22
Particle Count – 1.0 µm and greater	<= 10 par/ml	6

For Microelectronic Use

Reported value is the average of all samples counted for this lot number, with no individual sample value exceeding the specification.

Storage Conditions: Recommended Storage Conditions: 15° – 100°F
 Country of Origin: US
 Packaging Site: Paris Mfg Ctr & DC



Phillipsburg, NJ 9001:2008, 14001:2004
 Paris, KY 9001:2008
 Mexico City, Mexico 9001:2008
 Deventer, The Netherlands 9001:2008, 14001:2004, 13485:2003
 Gliwice, Poland 9001:2008, 17025:2005
 Selangor, Malaysia 9001:2008
 Dehradun, India, 9001:2008, 14001:2004, 13485:2003
 Mumbai, India, 9001:2008, 17025:2005
 Panoli, India 9001:2008



Richard M Siberski
 Vice President Global Quality