

Methanol
CMOS



Material No.: 9073-05
Batch No.: 0000020402
Manufactured Date: 2012/10/04
Retest Date: 2017/10/03

Certificate of Analysis

Test	Specification	Result
Assay (CH ₃ OH) (by GC)	>= 99.9 %	100.0
Color (APHA)	<= 10	5
Acidity (µeq/g)	<= 0.3	0.3
Alkalinity (µeq/g)	<= 0.1	0.1
Heavy Metals (as Pb)	<= 100 ppb	< 100
Residue after Evaporation	<= 5 ppm	4
Water (H ₂ O)(by Karl Fischer titrn)	<= 0.05 %	0.01
Solubility in H ₂ O	Passes Test	PT
Chloride (Cl)	<= 0.2 ppm	< 0.1
Phosphate (PO ₄)	<= 0.3 ppm	< 0.1
Sulfate (SO ₄)	<= 0.5 ppm	0.5
Trace Impurities – Aluminum (Al)	<= 50.0 ppb	< 5.0
Trace Impurities – Arsenic (As)	<= 5.0 ppb	< 2.0
Trace Impurities – Antimony (Sb)	<= 5.0 ppb	< 1.0
Trace Impurities – Barium (Ba)	<= 20.0 ppb	< 1.0
Trace Impurities – Boron (B)	<= 10.0 ppb	< 5.0
Trace Impurities – Cadmium (Cd)	<= 20.0 ppb	< 1.0
Trace Impurities – Calcium (Ca)	<= 50.0 ppb	1.9
Trace Impurities – Chromium (Cr)	<= 20.0 ppb	< 1.0
Trace Impurities – Cobalt (Co)	<= 20.0 ppb	< 1.0
Trace Impurities – Copper (Cu)	<= 10.0 ppb	< 1.0
Trace Impurities – Gallium (Ga)	<= 50.0 ppb	< 1.0
Trace Impurities – Germanium (Ge)	<= 50.0 ppb	< 10.0
Trace Impurities – Gold (Au)	<= 20.0 ppb	< 5.0

Test	Specification	Result
Trace Impurities – Iron (Fe)	<= 50.0 ppb	2.4
Trace Impurities – Lead (Pb)	<= 50.0 ppb	< 10.0
Trace Impurities – Lithium (Li)	<= 50.0 ppb	< 1.0
Trace Impurities – Magnesium (Mg)	<= 50.0 ppb	< 1.0
Trace Impurities – Manganese (Mn)	<= 10.0 ppb	< 1.0
Trace Impurities – Molybdenum (Mo)	<= 300.0 ppb	< 5.0
Trace Impurities – Nickel (Ni)	<= 10.0 ppb	< 5.0
Trace Impurities – Potassium (K)	<= 50.0 ppb	< 10.0
Trace Impurities – Silicon (Si)	<= 50.0 ppb	< 10.0
Trace Impurities – Silver (Ag)	<= 20.0 ppb	< 1.0
Trace Impurities – Sodium (Na)	<= 50.0 ppb	< 5.0
Trace Impurities – Strontium (Sr)	<= 10.0 ppb	< 1.0
Trace Impurities – Tin (Sn)	<= 50.0 ppb	< 10.0
Trace Impurities – Titanium (Ti)	<= 20.0 ppb	< 1.0
Trace Impurities – Vanadium (V)	<= 300.0 ppb	< 1.0
Trace Impurities – Zinc (Zn)	<= 50.0 ppb	< 1.0
Trace Impurities – Zirconium (Zr)	<= 300.0 ppb	< 1.0
Particle Count – 0.5 µm and greater	<= 100 par/ml	14
Particle Count – 1.0 µm and greater	<= 8 par/ml	6

For Microelectronic Use

Country of Origin: US
Packaging Site: Paris Mfg Ctr & DC

ISO

Phillipsburg, NJ 9001.2008, 14001.2004
Paris, KY 9001.2008
Mexico city, Mexico 9001.2008
Deventer, The Netherlands 9001.2008, 14001.2004
Selangor, Malaysia 9001.2008
Panoli, India 9001.2008
Gliwice, Poland 9001.2008, 17025.2005

Richard M Siberski

Richard M Siberski
Global Director of Quality Assurance