Acetic Acid, Glacial CMOS





Material No.: 9503-03 Batch No.: 0000051474 Manufactured Date: 2013/07/09 Retest Date: 2018/07/08

Certificate of Analysis

Test	Specification	Result
ssay (CH3COOH) (by freezing point)	>= 99.7 %	100.0
olor (APHA)	<= 10	5
cetic Anhydride ((CH3CO)2O)	<= 0.01 %	< 0.01
cetaldehyde	<= 0.05 %	< 0.01
esidue after Evaporation	<= 4 ppm	< 2
olubility in H₂O	Passes Test	РТ
pecific Gravity at 20°/20°C	>= 1.048	1.049
ubstances Reducing Dichromate	Passes Test	РТ
ubstances Reducing Permanganate	Passes Test	РТ
hloride (Cl)	<= 0.5 ppm	< 0.5
hosphate (PO4)	<= 0.5 ppm	< 0.3
ulfate (SO4)	<= 0.5 ppm	< 0.3
race Impurities – Aluminum (Al)	<= 50.0 ppb	< 5.0
rsenic and Antimony (as As)	<= 5 ppb	< 5
race Impurities – Barium (Ba)	<= 10.0 ppb	< 1.0
race Impurities – Beryllium (Be)	<= 10.0 ppb	< 1.0
race Impurities – Bismuth (Bi)	<= 50.0 ppb	< 10.0
race Impurities – Boron (B)	<= 10.0 ppb	< 5.0
race Impurities – Cadmium (Cd)	<= 10.0 ppb	< 1.0
race Impurities – Calcium (Ca)	<= 200.0 ppb	3.9
race Impurities – Chromium (Cr)	<= 30.0 ppb	1.3
race Impurities – Cobalt (Co)	<= 10.0 ppb	< 1.0
race Impurities – Copper (Cu)	<= 20.0 ppb	< 1.0
race Impurities – Gallium (Ga)	<= 10.0 ppb	< 1.0

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610

Test	Specification	Result
Frace Impurities – Germanium (Ge)	<= 10.0 ppb	< 10.0
Frace Impurities – Gold (Au)	<= 10.0 ppb	< 5.0
leavy Metals (as Pb)	<= 300 ppb	< 300
Frace Impurities – Iron (Fe)	<= 100.0 ppb	9.6
Frace Impurities – Lead (Pb)	<= 100.0 ppb	< 10.0
Frace Impurities – Lithium (Li)	<= 10.0 ppb	< 1.0
Frace Impurities – Magnesium (Mg)	<= 50.0 ppb	< 1.0
Frace Impurities – Manganese (Mn)	<= 10.0 ppb	< 1.0
Frace Impurities – Molybdenum (Mo)	<= 10.0 ppb	< 5.0
Frace Impurities – Nickel (Ni)	<= 25.0 ppb	< 5.0
Frace Impurities – Niobium (Nb)	<= 10.0 ppb	< 1.0
Frace Impurities – Potassium (K)	<= 100.0 ppb	< 10.0
Frace Impurities – Silicon (Si)	<= 50.0 ppb	< 10.0
Frace Impurities – Silver (Ag)	<= 10.0 ppb	< 1.0
Frace Impurities – Sodium (Na)	<= 100.0 ppb	< 5.0
Frace Impurities – Strontium (Sr)	<= 10.0 ppb	< 1.0
Frace Impurities – Tantalum (Ta)	<= 10.0 ppb	< 5.0
Frace Impurities – Thallium (TI)	<= 50.0 ppb	< 5.0
Frace Impurities – Tin (Sn)	<= 50.0 ppb	< 10.0
Frace Impurities – Titanium (Ti)	<= 100.0 ppb	< 1.0
Frace Impurities – Vanadium (V)	<= 10.0 ppb	< 1.0
Frace Impurities – Zinc (Zn)	<= 50.0 ppb	1.0
Frace Impurities – Zirconium (Zr)	<= 10.0 ppb	< 1.0
Particle Count – 1.0 µm and greater	<= 10 par/ml	4

For Microelectronic Use

Storage Conditions:IMPORTANT: Material will freeze if stored below 17 °C (63°F).Country of Origin:USPackaging Site:Paris Mfg Ctr & DC



Phillipsburg, NJ 9001:2008, 14001:2004 Paris, KY 9001:2008 Mexico City, Mexico 9001:2008 Deventer, The Netherlands 9001:2008, 14001:2004, 13485:2003 Gliwice, Poland 9001:2008, 17025:2005 Selangor, Malaysia 9001:2008, 14001:2004, 13485:2003 Mumbai, India, 9001:2008, 14001:2004, 13485:2003 Panoli, India 9001:2008

Nel M Sal

Richard M Siberski Global Director of Quality Assurance

For questions on this Certificate of Analysis please contact Technical Services at 855.282.6867 or +1.610.573.2600 Avantor ™ Performance Materials Inc.

3477 Corporate Parkway. Suite #200. Center Valley, PA 18034. U.S.A. Phone: 610.573.2600 . Fax: 610.573.2610