

Material No.: 9503-03
Batch No.: 0000247389
Manufactured Date: 2019/11/05
Retest Date: 2024/11/03
Revision No: 1

Certificate of Analysis

Test	Specification	Result
Assay (CH ₃ COOH) (by freezing point)	>= 99.7 %	100.0
Color (APHA)	<= 10	5
Acetic Anhydride ((CH ₃ CO) ₂ O)	<= 0.01 %	< 0.01
Acetaldehyde	<= 0.05 %	< 0.01
Residue after Evaporation	<= 4 ppm	< 1
Solubility in H ₂ O	Passes Test	PT
Specific Gravity at 20°/20°C	>= 1.048	1.051
Substances Reducing Dichromate	Passes Test	PT
Substances Reducing Permanganate	Passes Test	PT
Chloride (Cl)	<= 0.5 ppm	< 0.4
Phosphate (PO ₄)	<= 0.5 ppm	< 0.3
Sulfate (SO ₄)	<= 0.5 ppm	< 0.3
Trace Impurities – Aluminum (Al)	<= 50.0 ppb	2.0
Arsenic and Antimony (as As)	<= 5 ppb	< 5
Trace Impurities – Barium (Ba)	<= 10.0 ppb	< 0.2
Trace Impurities – Beryllium (Be)	<= 10.0 ppb	< 0.2
Trace Impurities – Bismuth (Bi)	<= 50.0 ppb	< 1.0
Trace Impurities – Boron (B)	<= 10.0 ppb	< 0.7
Trace Impurities – Cadmium (Cd)	<= 10.0 ppb	< 0.3
Trace Impurities – Calcium (Ca)	<= 200.0 ppb	43.0
Trace Impurities – Chromium (Cr)	<= 30.0 ppb	13.0
Trace Impurities – Cobalt (Co)	<= 10.0 ppb	< 0.3
Trace Impurities – Copper (Cu)	<= 20.0 ppb	2.0
Trace Impurities – Gallium (Ga)	<= 10.0 ppb	< 0.2

Test	Specification	Result
Trace Impurities – Germanium (Ge)	<= 10.0 ppb	< 2.0
Trace Impurities – Gold (Au)	<= 10.0 ppb	0.5
Heavy Metals (as Pb)	<= 300 ppb	< 300
Trace Impurities – Iron (Fe)	<= 100.0 ppb	27.0
Trace Impurities – Lead (Pb)	<= 100.0 ppb	3.0
Trace Impurities – Lithium (Li)	<= 10.0 ppb	< 0.2
Trace Impurities – Magnesium (Mg)	<= 50.0 ppb	7.0
Trace Impurities – Manganese (Mn)	<= 10.0 ppb	0.6
Trace Impurities – Molybdenum (Mo)	<= 10.0 ppb	< 3.0
Trace Impurities – Nickel (Ni)	<= 25.0 ppb	3.0
Trace Impurities – Niobium (Nb)	<= 10.0 ppb	< 0.2
Trace Impurities – Potassium (K)	<= 100.0 ppb	2.0
Trace Impurities – Silicon (Si)	<= 50.0 ppb	8.0
Trace Impurities – Silver (Ag)	<= 10.0 ppb	< 0.3
Trace Impurities – Sodium (Na)	<= 100.0 ppb	10.0
Trace Impurities – Strontium (Sr)	<= 10.0 ppb	< 0.2
Trace Impurities – Tantalum (Ta)	<= 10.0 ppb	< 0.9
Trace Impurities – Thallium (Tl)	<= 50.0 ppb	< 3.0
Trace Impurities – Tin (Sn)	<= 50.0 ppb	< 1.0
Trace Impurities – Titanium (Ti)	<= 100.0 ppb	0.2
Trace Impurities – Vanadium (V)	<= 10.0 ppb	< 0.2
Trace Impurities – Zinc (Zn)	<= 50.0 ppb	6.0
Trace Impurities – Zirconium (Zr)	<= 10.0 ppb	< 0.1
Particle Count – 1.0 µm and greater	<= 10 par/ml	4

For Microelectronic Use

For additional information, go to www.askavantor.com. Search keywords "freezing" and product name.

Storage Conditions: **IMPORTANT: Material will freeze if stored below 17 °C (63°F).**

Country of Origin: US

Packaging Site: Phillipsburg Mfg Ctr & DC



Jamie Ethier
 Vice President Global Quality