

Material No.: 5356-05 Batch No.: 24D1961013

Manufactured Date: 2024-04-15 Retest Date: 2029-04-14

Revision No.: 0

## Certificate of Analysis

Test	Specification	Result
Assay ((CH3)2CO) (by GC, corrected for water)	≥ 99.5 %	99.8 %
Color (APHA)	≤ 10	5
Residue after Evaporation	≤ 5 ppm	< 1 ppm
Acidity (µeq/g)	≤ 0.3	0.1
Alkalinity (µeq/g)	≤ 0.5	0.1
Water (H₂O)	≤ 0.5 %	0.2 %
Solubility in H₂O	Passes Test	Passes Test
Chloride (Cl)	≤ 0.2 ppm	< 0.2 ppm
Phosphate (PO4)	≤ 0.05 ppm	< 0.05 ppm
Trace Impurities - Aluminum (Al)	$\leq$ 50.0 ppb	< 5.0 ppb
Arsenic and Antimony (as As)	≤ 5.0 ppb	< 5.0 ppb
Trace Impurities – Barium (Ba)	$\leq 20.0 \text{ ppb}$	< 1.0 ppb
Trace Impurities - Boron (B)	$\leq 20.0 \text{ ppb}$	< 5.0 ppb
Trace Impurities - Calcium (Ca)	≤ 25.0 ppb	5.4 ppb
Trace Impurities – Chromium (Cr)	$\leq 20.0 \text{ ppb}$	< 1.0 ppb
Trace Impurities – Copper (Cu)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities - Gold (Au)	≤ 20 ppb	< 5 ppb
Trace Impurities – Iron (Fe)	$\leq 20.0 \text{ ppb}$	< 1.0 ppb
Trace Impurities – Lead (Pb)	$\leq 20.0 \text{ ppb}$	< 10.0 ppb
Trace Impurities – Lithium (Li)	$\leq$ 50.0 ppb	< 1.0 ppb
Trace Impurities – Magnesium (Mg)	≤ 20 ppb	< 1 ppb
Trace Impurities – Manganese (Mn)	≤ 10.0 ppb	< 1.0 ppb
Trace Impurities – Nickel (Ni)	≤ 10.0 ppb	< 5.0 ppb
Trace Impurities – Potassium (K)	≤ 50 ppb	< 10 ppb
Trace Impurities – Sodium (Na)	$\leq$ 50.0 ppb	< 5.0 ppb
Trace Impurities – Tin (Sn)	≤ 50 ppb	< 10 ppb
Trace Impurities – Titanium (Ti)	≤ 20 ppb	< 1 ppb
Trace Impurities – Zinc (Zn)	≤ 50 ppb	< 1 ppb

>>> Continued on page 2 >>>

Acetone VLSI



Material No.: 5356-05 Batch No.: 24D1961013

Test	Specification	Result	
Particle Count – 0.5 µm and greater	≤ 60 par/ml	7 par/ml	
Particle Count – 1.0 µm and greater	≤ 8 par/ml	3 par/ml	

For Microelectronic Use

Reported value is the average of all samples counted for this lot number, with no individual sample value exceeding the specification.

Country of Origin: USA

Packaging Site: Paris Mfg Ctr & DC



Sr. Manager, Quality Assurance