

Revision Date: 01-14-2016

SAFETY DATA SHEET

1. Identification

Product identifier: n-Butyl Alcohol

Other means of identification

Product No.: 9189, 9054, 2978, 3000

Recommended use and restriction on use

Recommended use: Not available.
Restrictions on use: Not known.

Details of the supplier of the safety data sheet

Manufacturer

Company Name: Avantor Performance Materials, Inc. Address: 3477 Corporate Parkway, Suite 200

Center Valley, PA 18034

Telephone: Customer Service: 855-282-6867

Fax: 610-573-2610

Contact Person: Environmental Health & Safety E-mail: info@avantormaterials.com

Emergency telephone number:

CHEMTREC: 1-800-424-9300 within US and Canada CHEMTREC: 1-703-527-3887 outside US and Canada

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Acute toxicity (Oral)

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Specific Target Organ Toxicity
Category 3

Category 3

Single Exposure

Specific Target Organ Toxicity - Category 2

Repeated Exposure

Label Elements

Hazard Symbol:



Signal Word: Warning



Revision Date: 01-14-2016

Hazard Statement: Flammable liquid and vapor.

Harmful if swallowed. Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statement

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-

ventilated area. Wash thoroughly after handling.

Response: In case of fire: Use water spray, foam, dry powder or carbon dioxide for

extinction. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Substances

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
N-BUTYL ALCOHOL		71-36-3	99 - 100%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

General information: Get medical advice/attention if you feel unwell. Show this safety data sheet

to the doctor in attendance.

Ingestion: Call a physician or poison control center immediately. Do NOT induce

vomiting.

Inhalation: Move to fresh air. Get medical attention if symptoms persist.



Revision Date: 01-14-2016

Skin Contact: Wash with soap and water. If skin irritation occurs: Get medical

advice/attention. Take off immediately all contaminated clothing. Wash

contaminated clothing before reuse.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms: Irritating to eyes, respiratory system and skin. Causes serious eye damage.

Narcotic effect.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed. Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards: Flammable liquid and vapor.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, foam, dry powder or carbon dioxide.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Heat may cause the containers to explode.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep unauthorized personnel away. Keep upwind. Use personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up:

Eliminate all ignition sources if safe to do so. Take precautionary measures against static discharges. Stop leak if possible without any risk. Use only non-sparking tools. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. Dike far ahead of larger spill for later recovery and disposal.



Revision Date: 01-14-2016

Notification Procedures: Prevent entry into waterways, sewer, basements or confined areas. Inform

authorities if large amounts are involved.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take precautionary measures against static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Wear protective gloves/protective clothing/eye

protection/face protection. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Keep away from food, drink and animal feeding stuffs. Keep container tightly closed in a cool, well-ventilated place. Ground container and transfer equipment to eliminate static electric sparks. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values		Source
N-BUTYL ALCOHOL	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	Ceil_Time	50 ppm	150 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	PEL	100 ppm	300 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	Ceiling	50 ppm	150 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	50 ppm	150 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		61 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (12 2010)
	ST ESL		610 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (12 2010)
	ST ESL		200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (12 2010)
	AN ESL		20 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (12 2010)
	Ceiling	50 ppm	150 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)

Appropriate Engineering Controls

No data available.



Revision Date: 01-14-2016

Individual protection measures, such as personal protective equipment

General information: Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. An eye wash and safety shower must be available in the

immediate work area. Use explosion-proof ventilation equipment.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Chemical resistant gloves

Other: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Provide eyewash station and safety shower.

0.8098 (4 °C)

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Colorless
Odor: Characteristic
Odor threshold: No data available.
pH: No data available.

Melting point/freezing point: -89.8 °C Initial boiling point and boiling range: 118 °C

Flash Point: 37 °C (Closed Cup)
Evaporation rate: 0.46 (butyl acetate=1)
Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 11.25 %(V)
Flammability limit - lower (%): 1.45 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

Vapor density:

No data available.

No data available.

0.9 kPa (25 °C)

2.6 AIR=1

Solubility(ies)

Relative density:

Solubility in water: 90 g/l

Solubility (other):No data available.

Partition coefficient (n-octanol/water): 0.88

Auto-ignition temperature: 650 °F

Decomposition temperature:No data available. **Viscosity:**No data available.

Other information



Revision Date: 01-14-2016

Molecular weight: 74.12 g/mol (C4H10O)

10. Stability and reactivity

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Hazardous polymerization does not occur.

Conditions to avoid: Heat, sparks, flames. Contact with incompatible materials.

Incompatible Materials: Strong oxidizing agents. Acids. Aldehydes. Isocyanates.

Hazardous Decomposition

Products:

Thermal decomposition may release oxides of carbon.

11. Toxicological information

Information on likely routes of exposure

Ingestion: Harmful if swallowed.

Inhalation: May cause irritation to the respiratory system. May cause drowsiness or

dizziness.

Skin Contact: May be harmful in contact with skin. Causes skin irritation.

Eye contact: Causes serious eye damage.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: LD 50 (Rat): 790 mg/kg

Dermal

Product: LD 50 (Rabbit): 3,400 mg/kg

Inhalation

Product: LC 50 (Rat, 4 h): 8000 ppm

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: May be harmful in contact with skin. Causes skin irritation.

Serious Eye Damage/Eye Irritation

Product: Causes serious eye damage.

Respiratory or Skin Sensitization

Product: Not a skin sensitizer.

Carcinogenicity

Product: No data available.



Revision Date: 01-14-2016

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No mutagenic components identified

In vivo

Product: No mutagenic components identified

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: Narcotic effect. Respiratory tract irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: Blood, Central nervous system. - May cause damage to organs through

prolonged or repeated exposure.

Aspiration Hazard

Product: May be harmful if swallowed and enters airways.

Other effects: None known.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

N-BUTYL ALCOHOL LC 50 (Bluegill (Lepomis macrochirus), 96 h): 100 - 500 mg/l Mortality

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 1,910 mg/l Mortality

LC 50 (Carp (Leuciscus idus melanotus), 48 h): 1,200 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

N-BUTYL ALCOHOL LC 50 (Water flea (Daphnia magna), 24 h): 1,855 mg/l Mortality

LC 50 (Brine shrimp (Artemia salina), 24 h): 2,950 mg/l Mortality

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.



Revision Date: 01-14-2016

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: There are no data on the degradability of this product.

BOD/COD Ratio

Product: No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product: Rainbow trout, donaldson trout (Oncorhynchus mykiss), Bioconcentration

Factor (BCF): 0.38 (Static)

Partition Coefficient n-octanol / water (log Kow)

Product: Log Kow: 0.88

Mobility in Soil: The product is partly soluble in water. May spread in the aquatic

environment.

Other Adverse Effects: The product components are not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills

can have a harmful or damaging effect on the environment.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and

product characteristics at time of disposal.

Contaminated Packaging: Since emptied containers retain product residue, follow label warnings even

after container is emptied.

14. Transport information

DOT

UN Number: UN 1120 UN Proper Shipping Name: Butanols

Transport Hazard Class(es)

Class(es): 3
Label(s): 3
Packing Group: III

Marine Pollutant: Not a Marine Pollutant

Special precautions for user: –



Revision Date: 01-14-2016

IMDG

UN Number: UN 1120 UN Proper Shipping Name: BUTANOLS

Transport Hazard Class(es)

 Class(es):
 3

 Label(s):
 3

 EmS No.:
 F

EmS No.: F-E, S-D

Packing Group:

Marine Pollutant: Not a Marine Pollutant

Special precautions for user: –

IATA

UN Number: UN 1120 Proper Shipping Name: Butanols

Transport Hazard Class(es):

Class(es): 3 Label(s): 3

Marine Pollutant: Not a Marine Pollutant

Packing Group: III Special precautions for user: –

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

N-BUTYL ALCOHOL 5000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Acute (Immediate) Chronic (Delayed)

Fire

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity Reportable quantity

N-BUTYL ALCOHOL 5000 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u> <u>Threshold Planning Quantity</u>

N-BUTYL ALCOHOL 10000 lbs

SARA 313 (TRI Reporting)

Reporting Reporting threshold for manufacturing and

Chemical Identityother usersprocessingN-BUTYL ALCOHOL10000 lbs25000 lbs.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

None present or none present in regulated quantities.



Revision Date: 01-14-2016

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

N-BUTYL ALCOHOL

US. Massachusetts RTK - Substance List

Chemical Identity

N-BUTYL ALCOHOL

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

N-BUTYL ALCOHOL


US. Rhode Island RTK

Chemical Identity

N-BUTYL ALCOHOL

16.Other information, including date of preparation or last revision

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

Issue Date: 01-14-2016

Revision Date: No data available.

Version #: 2.1

Further Information: No data available.



Revision Date: 01-14-2016

Disclaimer:

THE INFORMATION PRESENTED IN THIS MATERIAL SAFETY DATA SHEET (MSDS/SDS) WAS PREPARED BY TECHNICAL PERSONNEL BASED ON DATA THAT THEY BELIEVE IN THEIR GOOD FAITH JUDGMENT IS ACCURATE. HOWEVER, THE INFORMATION PROVIDED HEREIN IS PROVIDED "AS IS," AND AVANTOR PERFORMANCE MATERIALS MAKES AND GIVES NO REPRESENTATIONS OR WARRANTIES WHATSOEVER, AND EXPRESSLY DISCLAIMS ALL WARRANTIES REGARDING SUCH INFORMATION AND THE PRODUCT TO WHICH IT RELATES, WHETHER EXPRESS, IMPLIED, OR STATUTORY, INCLUDING WITHOUT LIMITATION, WARRANTIES OF ACCURACY, COMPLETENESS, MERCHANTABILITY, NON-INFRINGEMENT, PERFORMANCE, SAFETY, SUITABILITY, STABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, AND ANY WARRANTIES ARISING FROM COURSE OF DEALING, COURSE OF PERFORMANCE. OR USAGE OF TRADE. THIS MSDS/SDS IS INTENDED ONLY AS A GUIDE TO THE APPROPRIATE PRECAUTIONARY HANDLING OF THE MATERIAL BY A PROPERLY TRAINED PERSON USING THIS PRODUCT, AND IS NOT INTENDED TO BE COMPREHENSIVE AS TO THE MANNER AND CONDITIONS OF USE, HANDLING, STORAGE, OR DISPOSAL OF THE PRODUCT. INDIVIDUALS RECEIVING THIS MSDS/SDS MUST ALWAYS EXERCISE THEIR OWN INDEPENDENT JUDGMENT IN DETERMINING THE APPROPRIATENESS OF SUCH ISSUES. ACCORDINGLY, AVANTOR PERFORMANCE MATERIALS ASSUMES NO LIABILITY WHATSOEVER FOR THE USE OF OR RELIANCE UPON THIS INFORMATION. NO SUGGESTIONS FOR USE ARE INTENDED AS, AND NOTHING HEREIN SHALL BE CONSTRUED AS, A RECOMMENDATION TO INFRINGE ANY EXISTING PATENTS OR TO VIOLATE ANY FEDERAL, STATE, LOCAL, OR FOREIGN LAWS. AVANTOR PERFORMANCE MATERIALS REMINDS YOU THAT IT IS YOUR LEGAL DUTY TO MAKE ALL INFORMATION IN THIS MSDS/SDS AVAILABLE TO YOUR EMPLOYEES.